www.wulftec.com

Technical Specifications

	 1								
Turntable – Low Profile			Standard SML-200)			Standard with extended bas (SML-EXT)			
CAPACITY	4,000 lb.		5,000 lb.		5,000 lb.		5,000 lb.		
Motor	1/2 HP		3/4 HP		1 HP		1 HP		
RPM	12 RPM		12 RPM		12 RPM			12 RPM	
TURNTABLE SIZE	58" dia.		65" dia.		65" dia.			77" dia.	
MAX LOAD SIZE	50"W x 50"L (70.7 dia.)		55"W x 55"L (78 dia.)		55"W x 55"L (78 dia.)		ia.)) 65"W x 65"L (92 dia.)	
FORKLIFT PORTABLE DESIGN	Yes		Yes		Yes			Yes	
RAMP ACCESS AVAILABLE ON THREE SIDES	Yes		Yes		Yes			Yes	
Turntable – High Profile			Split-base (SMH-SPL)		Standard (SMH-200)		Extra heavy-duty (SMH-HVY)		
CAPACITY	4,000 lb. 5		5,000 lb.		5,000 lb.		8,000 lb.		0 lb.
Motor	3/4 HP 3		3/4 HP		3/4 HP		1 HP).
RPM	12 RPM		12 RPM		12 RPM		12 RPM		PM
TURNTABLE SIZE	51" dia.		51" dia.		51" dia.		51" dia.		lia.
MAX LOAD SIZE	58"W x 58"L (82 dia.)		58"W x 58"L (82 dia.)		58"W x 58"L (82 d		dia.) 58"W x 58"L (82 dia.)		V x 58"L (82 dia.)
FORKLIFT PORTABLE DESIGN	Yes		es		Yes		Yes		
Wrap Height Options	80" (std) 92"			104"		116"	128"		128"
LOW PROFILE TURNTABLE	Yes Yes			Yes		Yes		Yes	
HIGH PROFILE TURNTABLE	Yes	Yes		Yes		Yes		N/A	
Carriage	Film size								
NO-THREAD® POWERED PRE-STRETCH	20" or 30"								
NO PRE-STRETCH CARRIAGE	20" or 30"								
Control Panel	Basic panel (B)	Stan	Standard panel (S)			Deluxe panel (D)			
CONTROL UNIT	Allen Bradley PLC		Allen I	Allen Bradley PLC			Allen Bradley PLC Panel View touch screen		
TOP AND BOTTOM WRAP SELECTORS	1-3		0-9 (separate top and bottom wrap selectors)			0-10 (separate top and bottom wrap selectors)			
SEPARATE UP/DOWN CARRIAGE SPEEDS	One speed		Yes	Yes			Yes		
SPIRAL UP	N/A	Yes	Yes			Yes			
SPIRAL UP/DOWN	Yes	Yes	Yes				Yes		
AUTOHEIGHT SENSING PHOTOEYE	Yes	Yes	Yes			Yes			
REINFORCED WRAP/MANUAL ROTATION	Yes	Yes	Yes			Yes			
TOP COVER PAUSE SWITCH (SPLASH-PROOF PROGRAM)	N/A	Yes	Yes			Yes			

All units will wrap up to 50 loads per hour. Approximate shipping weight is 1,200 lbs. to 2,800 lbs



WULFTEC

209 Wulftec, Ayer's Cliff, Quebec, Canada J0B 1C0

Tel: (819) 838-4232

Toll Free: 1-877-WULFTEC (985-3832)

Fax: (819) 838-5539

E-mail: wulftec@wulftec.com

SMART

M. J. MAILLIS

YEAR WARRANTY **WULFTEC®**

Semi-Automatic Turntable Stretch Wrappers









Get the exact stretch wrapper you need

Pay only for the features you want

... Now THAT'S SMART

SML-150 SML-200 SML-EXT SML-277 SMH-150 SMH-SPL SMH-200 SMH-HVY Pay only for what you need.




Extremely affordable.

Quick turnaround.

Adapting without overspending.

Featuring Allen Bradley variable frequency drives:



- > ACCURATE SPEED CONTROL
- > EASY DIGITAL READOUT
- > EXCELLENT REPEATABILITY OF SETTINGS
- > MAINTENANCE FREE

SUPERIOR FEATURES THAT ARE JUST PLAIN SMART

- Larger diameter heavy-duty turntables
- Larger weight capacity machines
- Enclosed dual #50 carriage lifting chains for increased safety
- Enclosed carriage lift motor for better protection
- Side-mounted carriage for optimal film
- · Quick disconnect throughout for ease of installation and maintenance
- NEMA 4/12 panel enclosures

For every need, there's a SMART SOLUTION

NEED:

A basic stretch wrapper that can wrap 80" high loads.

SMART SOLUTION:

Model SML-150-B

A 58", 4,000 lb. capacity octagonal low-profile turntable equipped with a 80" wrap height tower, 20" NO-THREAD® powered pre-stretch carriage and basic control panel.

Get SMART in 4 easy steps

Step 1: CHOOSE YOUR TURNTABLE

Low Profile - Choice of 4 Models



CHOICE OF 2 MODELS

optimal film delivery

FEATURES:

Octagonal base (SML-150) 58" diameter, 4,000 lb. capacity Max load size 50"W x 50"L (70.7" dia.)

Standard base (SML-200) 65" diameter, 5,000 lb. capacity Max load size 55"W x 55"L (78" dia.)

Standard 2' extension base (SML-EXT) 65" diameter, 5,000 lb. capacity Max load size 55"W x 55"L (78" dia.)

Step 3: CHOOSE YOUR CARRIAGE

Oversized base (SML-277) 77" diameter, 5,000 lb. capacity Max load size 65"W x 65"L (92" dia.)

20" or 30" NO-THREAD® powered pre-stretch

20" or 30" no pre-stretch carriage (ideal for

Carriage located on the side of the tower for


Pre-stretch rollers' blue compound are

carriage (50-300% pre-stretch ratio)


netting or pre-stretched film)

covered by a lifetime warranty

HIGH PROFILE - CHOICE OF 4 MODELS



Octagonal base (SMH-150) 51" width, 4,000 lb. capacity Max load size 58"W x 58"L (82" dia.)



Standard base (SMH-200) 51" width, 5,000 lb. capacity Max load size 58"W x 58"L (82" dia.)

Extra heavy-duty base (SMH-HVY) 51" width, 8,000 lb. capacity ring-gear driven (10-year warranty) Max load size 58"W x 58"L (82" dia.)

Step 2: CHOOSE YOUR WRAP HEIGHT



Choice of heights:

V		
V	LP:	HP:
	80"	80"
Γ	92"	92"
	104"	104"
1	116"	116"
ш	128"	
Ш	Features:	

- > Heavy-duty tower with enclosed dual #50 carriage lifting chains and motor for greater safety and protection
- >Quick disconnect for easy installation and maintenance

Step 4: CHOOSE YOUR CONTROL PANEL

CHOICE OF 3 PANELS

(see control panel sheet for more details) All panel enclosures are NEMA 4/12

BASIC PANEL (B)



> Allen Bradley PLC > Basic wrapping

STANDARD PANEL (S)



Allen Bradley PLC

program changes

Advanced wrapping functions Allows for some options and minor

DELUXE PANEL (D)



- Panel View touch screen > Highly flexible wrapping
- > Allows for a full range of options and program changes

www.wulftec.com

Resistant blue compound

No pre-stretch carriage - for



Unbeatable performance

Wulftec® stretch wrappers are well-known for their exceptional strength, durability and reliability -- no matter how harsh your environment may be.

NEED HELP CHOOSING?

Call us at 1-877-WULFTEC (985-3832)

or contact your Wulftec Distributor



Looking for a SMART

stretch wrapping solution?

The SMART™ machine has been designed to allow you to:

- > upgrade the control panel at any time
- > upgrade the base at any time
- > upgrade the carriage at any time
- > change out the tower height at any time

Pretty SMART, don't you think?

THE WULFTEC ADVANTAGE:

- > Allen Bradley PLC for more flexibility
- > AC variable frequency drives and
- > Heavy-duty steel construction
- NO-THREAD powered pre-stretch
- > Superior warranties:



- LIFETIME warranty on pre-stretch rollers' blue compound
- 10-year warranty on structural frame
- 4-year unlimited cycle warranty

For every need, there's a SMART SOLUTION

A heavy-duty turntable to handle a 6,000 lb. load with a full range of wrapping patterns and the possibility to do program changes later.

SMART SOLUTION:

Model SMH-HVY-D

A extra heavy-duty 51", 8,000 lb. capacity highprofile ring-gear driven turntable equipped with an 80" wrap height tower, 20" NO-THREAD® powered pre-stretch carriage and a deluxe control panel.