

NEW!

The ValueLine pallet wrappers are designed to meet the most cost effective pallet wrapping applications. The function of the machines are to easily and effectively wrap pallets with palletized goods on them, secure enough for transportation.

Designed with affordability, versatility and reliability in mind, the ValueLine machines ensure maximum efficiency while cutting labor and stretch film costs. A step above hand wrapping.

- IDEAL FOR LOW VOLUME USERS IN ALL INDUSTRIES
- EASY MACHINE SET-UP FOR FIRST TIME USERS
- SIMPLE AND EASY TO USE CONTROL PANEL
- FOLD DOWN TOWER FOR EASE OF INSTALLATION AND TRANSPORT

Eliminate Labor & Injuries - Plus, Save on Film Usage

Eliminate Labor & Injuries By Not Hand Wrapping

PERFECT FOR PRE-STRETCHED FILM OR NETTING

POWERED PRE-STRETCH UP TO 300%

WVL-100

WVL-075



Technical Specifications

| | WVL-100 | WVL-075 |
|------------------------------------|---|--|
| PRODUCTION RATE* | • Up to 40 loads per hour | • Up to 40 loads per hour |
| MACHINE DIMENSIONS | • 58"W x 100"L x 90 3/4"H | • 59"W x 92"L x 101"H |
| LOAD SIZE | • 50"W x 50"L x 80"H (70.7" diagonal) | • 50"W x 50"L x 80"H |
| LOAD WEIGHT | • Up to 3,000 lbs. | • Up to 3,000 lbs. |
| APPROXIMATE SHIPPING WEIGHT | • 985 lbs. | • 970 lbs. |
| ELECTRICAL REQUIREMENTS | • 120V/1/60 15A | • 120V/1/60 15A |
| WRAP HEIGHTS | • 80" wrap height | • 80" wrap height |
| CONTROLS | <ul style="list-style-type: none"> • Programmable logic controller (PLC) • 24V control system • Current overload protection • Autoheight sensing photoeye • Power on/off switch and indicator light • Start/stop push button • Large emergency stop (push pull type) • Variable AC frequency drives • Manual carriage up/down function • Table jog • Variable table speed (10 RPM) • Carriage speed adjustment • Top and bottom wrap selectors – one selector for 1, 2, 3 • Film tension adjustment • Carriage limits: prox for down and limit switch for up | <ul style="list-style-type: none"> • Manual and automatic mode • Two automatic wrapping cycles • Manual carriage up and down switch • Film overlap control • Turntable speed adjustment • Top and bottom wraps • Power on/off switch • Start/stop button |
| FILM DELIVERY SYSTEM | <ul style="list-style-type: none"> • 20" NO-THREAD® Powered Pre-Stretch Carriage • AC motor and 120V AC drive • Lifetime warranty on pre-stretch rollers' blue compound • Film force release for easy pull at start and end of cycle • 200% pre-stretch ratio (other pre-stretch ratio sold separately) • Electronic film tension control with analog sensor • Lexan roller cover for operator safety | <ul style="list-style-type: none"> • Adjustable mechanical tensioning brake • Easy film threading |
| FILM CARRIAGE DRIVE | <ul style="list-style-type: none"> • AC motor and 120V AC drive • Belt driven with safety detection device | • Chain driven |
| TURNTABLE | • 58" dia. turntable | • 58" dia. turntable |
| TURNTABLE DRIVE | <ul style="list-style-type: none"> • 0-10 RPM variable speed • AC motor with 120V AC drive • Chain driven turntable • Electronic soft start/stop • Positive turntable alignment controlled by proximity sensor | <ul style="list-style-type: none"> • 0-10 RPM • Chain driven turntable |
| STRUCTURE | <ul style="list-style-type: none"> • Steel tower • Forklift portable base design – from one side • Structural steel construction | <ul style="list-style-type: none"> • Steel tower • Structural steel construction |
| TECHNICAL INFORMATION | • The machine is provided with a manual including electro/mechanical schematics and drawings, troubleshooting guide & installation instructions | • The machine is provided with a manual including electro/mechanical schematics and drawings, troubleshooting guide & installation instructions |
| WARRANTY | <ul style="list-style-type: none"> • 1 year • Lifetime warranty on pre-stretch rollers' blue compound | • 1 year |



WVL-100
20" NO-THREAD® POWERED PRE-STRETCH CARRIAGE
LIFETIME WARRANTY ON PRE-STRETCH ROLLERS' BLUE COMPOUND



WVL-075
NO PRE-STRETCH CARRIAGE



WVL-100 PANEL



WVL-075 PANEL

M. J. MAILLIS

SOLD THROUGH:
 Wulftec International Inc.
 209 Wulftec, Ayer's Cliff, Quebec, Canada
 J0B 1C0
 Tel: 819 838-4232
 Toll Free: 1 877 WULFTEC (985-3832)
 Fax: 819 838-5539
 E-mail: wulftec@wulftec.com